

KEY FEATURES

- High power handling: 2.000 W program power
- 4" voice coil
- High sensitivity: 96 dB (1W / 1m)
- FEA optimized magnetic circuit
- Low power compression losses
- Weatherproof cone with treatment for both sides of the cone
- High excursion capabilities: $X_{\max} \pm 12,5$ mm
- Low frequency extension, deep sound and high control



TECHNICAL SPECIFICATIONS

Nominal diameter	460 mm	18 in
Rated impedance		8 Ω
Minimum impedance		6,8 Ω
Power capacity ¹	1.000 W _{AES}	
Program power ²	2.000 W	
Sensitivity	96 dB	1W / 1m @ Z _N
Frequency range	30 - 2.000 Hz	
Recom. enclosure	V _b = 200 l	
(Bass Reflex Desing)	F _b = 35Hz	
Voice coil diameter	101,6 mm	4 in
BI factor		25 N/A
Moving mass	0,245 kg	
Voice coil length	30 mm	
Air gap height	12 mm	
X _{damage} (peak to peak)	52 mm	

Notes:

¹ The power capacity is determined according to AES2-1984 (r2003) standard.


² Program power is defined as power capacity + 3 dB.

³ T-S parameters are measured after an exercise period using a preconditioning power test. The measurements are carried out with a velocity-current laser transducer and will reflect the long term parameters (once the loudspeaker has been working for a short period of time).

⁴ The X_{max} is calculated as (L_{vc} - H_{ag})/2 + (H_{ag}/3,5), where L_{vc} is the voice coil length and H_{ag} is the air gap height.

THIELE-SMALL PARAMETERS³

Resonant frequency, f _s	27 Hz
D.C. Voice coil resistance, R _e	6 Ω
Mechanical Quality Factor, Q _{ms}	8,2
Electrical Quality Factor, Q _{es}	0,40
Total Quality Factor, Q _{ts}	0,38
Equivalent Air Volume to C _{ms} , V _{as}	317 l
Mechanical Compliance, C _{ms}	142 μ m / N
Mechanical Resistance, R _{ms}	5,1 kg / s
Efficiency, η_0	1,5 %
Effective Surface Area, S _d	0,1255 m ²
Maximum Displacement, X _{max} ⁴	12,5 mm
Displacement Volume, V _d	1.560 cm ³
Voice Coil Inductance, L _e	2 mH



Note: On axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1W @ 1m

MOUNTING INFORMATION

Overall diameter	461 mm	18,1 in
Bolt circle diameter	438 mm	17,2 in
Baffle cutout diameter:		
- Front mount	415 mm	16,4 in
Depth	212 mm	8,4 in
Net weight	13,5 kg	30 lb
Shipping weight	15,1 kg	33,9 lb

DIMENSION DRAWING

